



RP 80- V1 Linerless label/Receipt Printing



Print Specifications	Print width 48mm & 72mm/Paperwidth 58mm & 80mm/203dpi, Label thickness - 0.06~0.15mm/Roll dia - 80mm max/Easy Paper Loading/ Print Speed - 350mm/sec
Print Font/Barcode	Support any Languages
Storage Specification	FLASH: 4MB, RAM: 8MB
Media Type	Receipt paper/Multiplex Ticketing (Black Mask Sensor) / Linerless Label Printing
Power Source	24V/2.5A.
Interface	Default USB - Optional USB+Serial+Ethernet
Printing Command	ESC/Windows Driver/OPOS
Barcode & Graphic Support/Other Features	Big Gear Long Life, Durable Performance, Wall hanging option, Flash light when receive order, Voice reminding, NFC Function (Optional)
Printer Dimension(LxVxH)	200*146*140mm
Environment	Working temperature: 0~40°C; Storage temperature: -20~70 Working humidity: 20~85%; Storage temperature: 5~95%

Solutions



Quick Service Restaurant



Parking Lot



Multiplex Ticketing



Food Delivery



Lottery



Visitor Management

Application

Receipt, Food delivery, Address Label, Product Label, Cinema Ticket, Visitor Stickers through Linerless Re-Stick Label