



# RP-76III

## 3-inch Impact Receipt Printer

- Serial Impact dot matrix printer
- Bi-directional printing
- Thermal Receipt Printer
- Suitable for all verticals



### Specification

Printing Method	9 pins serial impact dot matrix with easy paper loading
Printing Speed	4.4 lines/s; Bi-direction Printing : 2.1 lines/s
Columns per line	7×9dots:40; 9×9dots:33; 16×16dots:21
Double Color Printing	Optional
Paper Width	76 mm±0.5mm
Self-defining Character	Support
Font	Standard Font Level 3 : 16×16dots
Western Language	ASCII : 7×9dots, 9×9dots
	Serial, Parallel, Ethernet, USB
Function	Paper Out Alarm, Open Alarm, Black Mark Detection, Over Heating Protection, Hummer
Cash Drawer Port	DC24V, 1A, 6 LineRJ-11 Sector
Ribbon cassette	Brown/black/ red and black double ribbon
Direct-current	DC24V±10 %, 2.5A
Paper Type	High Quality Normal White Paper or Impact Paper Roll 76x Ø 80mm
Paper Thickness	0.06mm~ 0.08mm
Paper Loading	Easy
Paper Cutting Way	Manual Tearing or Auto Cutter(Full or half optional)
Dimension	250mmX156mmX128mm
Weight	2250g (Exclusive of Paper Roll)
Operating Temperature	0 ~50 OC/ 10% ~ 80% RH
Storage Temperature/Humidity	-20~ 60 OC , 10%~90% RH
Mechanical Reliability	7.5 million lines (MCCBF)
Printing head	1.5 Million words
Cutter	1 million times