

All-In-One Handheld POS Terminal



RP 6s



Lightweight, Integrated and Ergonomic Design for Easy Handling

Retail POS RP series are a Lightweight Integrated Terminals with all the modules required for a Mobile Point of Sale built into a sleek monolithic design. It houses an optional Aadhar Compliant Fingerprint Scanner, a 2" Thermal Printer, 2D Barcode Scanner, Magnetic Swipe Card Reader (MSR), Contact and Contactless IC Card Reader and COTS Ready NFC Reader for Contactless Payment Acceptance.

RP 6s

Specifications	RP 6s
Operating systems	Android OS 7.1
Processor	Snapdragon A-53, 1.4Ghz Quad core
Memory and Storage	Default 2GB/16GB eMMC optional 3GB/32GB eMMC
Display	5.99 IPS PCAP Multi Touch (Virtual Keypad support), Day light readable 170° viewing angle
Resolution	Supports 1440 x 720 pixels
Contrast & Brightness	1000:1, 330 cd/m ²
Camera	5MP Rear with Manual & AF
Scanning Options	Inbuilt Camera Supports Decode of all linear 1D & 2D/QR Barcodes
Scan Engine	Optional Module supports scanning of 1D & 2D /Matrix/QR Barcode Symbology
Communications	Wireless LAN : Dual Band 2.4GHz / 5GHz supports IEEE 802.11 a/b/n/g, Bluetooth : 2.1/3.0/4.2 BLE support Supports AGPS & GPS, Glonass GSM : 2G/3G/4G support
Card Slots	1 X PSAM / 1 X Mini SIM / +eSIM support
Ports	USB C Type (Supports OTG and USB Charging)
Reader Modules	COTS Ready NFC module supports type A & B mifare / Felica Card, ISO/ICE 14443 & ISO 15693 compliant.
Printer	Thermal 203dpi, speed: 50 ~ 70 mm/sec, Print width : Max 58mm, paper roll dia 40mm
Charging / Standby	Base Cradle (optional) or Power adaptor (100~240V input, DC output 5V, 2A) through type C cable. Charging Time : Full Charge in 4 hours. Standby Time : 10 Days (Dark Screen)
Battery Capacity & Working	Field Replaceable Battery with capacity (3.8V/2580mAh x 2) 7.6V/5160mAh , optional One full charge of spare battery power bank supports continuous 24 Hours operation.
Speaker & Mic	1W / Mic input
Accessories (Optional)	Battery Power Bank(MI), Cradle Modle:DS6 (Brand: Rugtek), LCD Protection Film & Power Adaptor (5V±2A)
Physical Characteristics	Dimensions: 215.2 x 83 x 17 in mm (Wt: 360 Gms without receipt roll)
Environmental	Operating temperature: 0°C~45°C/ Storage temperature: -40°C~70°C
Durability	With Rubber boot design supports 1 Mtr Drop resistance (also protects corner)
Product Life Support	Available on request for 3 to 5yrs including OS & Security feature upgrades. Optional MDM supports device locking & launch only billing application, remote management, application upgrades etc

Optional Accessories



Standard
Battery / Power bank



Cradle DS6

Solutions



Van Sales



Traffic Offence e-Challan



Cafe/Food Court



Parking Bills



Government Utility

Certifications



RUGTEK

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD

7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru,
Karnataka 560093

Tel : 080-40782700

E-mail : marketing@posiflexindia.com

Mob : +91 9535 432110

Website : www.rugtek.com

Authorized Distributor / Reseller

