



BP-02

Portable Bluetooth Printer

- Mini size, Lightweight , Durable performance
- Quick charge with Rechargeable Li-ion Battery
- Dual Connectivity for fast and easy data transfer
- Thermal Receipt Printer



Windows



Android



Linux

Specification

Print Way	Thermal sensitive line dot method
Paper Width	56mm
Printing thickness	60 ~ 80µm
Valid printing width	48mm
Resolution	8 dot/mm(230 dpi)
Dot/Line	384 dots
Printing Speed	50-80 mm/s
Printing content	Support any language
Outer dimension	103 x 75 x 46 mm
Weight	340g
Rolling paper Diameter	≤30.5mm
Interface	Original IR(RAW_IR), VIR, IrDA (IrCOMM) RS232 port, Bluetooth, USB interfaces varied between different models.
Environment Parameters	Working temperature: -10°C ~ 50°C Working humidity: 20% ~ 85% Storing temperature : -20°C ~ 70°C Storing humidity: 5% ~ 95%
Paper feeding method	Easy paper loading
Mark position	detecting mark position
Paper sensor	An LED indicator flashes when the paper runs out, and an alarm sounds.
Printing Command	ESC/POS compatible with commands set
Power	1600 / 2100 mAh rechargeable li-ion battery
Power alarm	When the battery is low, the indicator flashes and the printer gives two short hoots. The buzzer will also sound repeatedly to indicate charging time.