

2D Handheld Barcode Scanner with stand option

RS - 3200



Image(Pixels)	1280 pixels(H)*800 pixels(v) 1Million Pixels
Light Source	Aiming: 617 nm White LED; illumination:6500K White LED
Depth of Field	40-250mm@UPC/EAN 13mil PCS=90%;20-250mm@QR 20mil PCS=100% ; 20mm -300 mm @ 20mil
Scan Angle/Speed	Elevation angle 65°/Tilt angle 30°/Declination 55° ; 350 scans/sec
Field of view	34° horizontal, 28° vertical
Read Resolution	More than 4 mil
Print Contrast	More than 25%
Visual Indicator	Blue LED Lights , Buzzer
Communication Interfaces	USB/RS-232 (HID-KBW Or Virtual Serial Port)
Beeper Operation	Programmable tone & Volume
Dimension H x W X L	173mm*67mm*94mm (Length x Width x Height)
Weight	220g (With Cable) / 190G (Without cable)
Material	ABS + PC
Cable	Standard 1.8M straight
Input Voltage	5VDC±10%
Working current	80-170mA(min/max)
Laser Class	CE EN55022 B, FCC Part 15 Class B, VCCI, BSMI
EMC	CDRH Class II, IEC 60825-1 Class 1
Operating Temperature	-20°C to 60°C
Storage Temperature	-40°C to 70°C
Working Humidity	5% to 95% relative humidity, non-condensing
Ambient Brightness	0 to 100,000 Lux (Daylight)
Drop Durability	Designed to withstand 5 Meters drop
Decode Capability	2D: QR Code, Data Matrix, PDF417,Aztec, Maxicode, etc. 1D: UPC/EAN/JAN,UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 &JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128, Code 93, Interleaved 2 of 5 (ITF),Addendum 2 of 5, IATA Code, MSI/Plessey, China Postal Code,Code 32 (Italian Pharmacode), RSS 14, RSS Limited, RSS Expanded
IP Level	IP54
Drivers	Linux/Win/U-POS
BIS Number	CRS 2020-0031/R-41151041
Warranty	3 year against manufacturing defects

V1.1_17042021