



RP-82

Cube Printer













Specification

Print	
Printing Method	Thermal line/Support QR code Printing
Printing Setup	Support header margin adjustment, support line spacing, the width of the receipt,
	barcode height adjustment
Printing Speed	250mm/s
Resolution	203dpi
Paper Width	72mm/48mm
Paper compartment Capacity	80mm
Cutter	Support (support paper back when finish cutting)
SD RAM	8MB
FLASH	4MB
Network	
with wire	TCP/IP Ethernet interface (10M/100M) +USB
wireless	802.11 b/g/n, BT4.0 BLE (Optional)
NFC	Optional (only support Wireless)
Outside interface	
Cash Drawer	1*RJ11, 1*USB Standard/ethernet
key	Power Key/Cover key/Feed Key
Light	Monochromatic lamp
Voice	buzzer, suona
Power	Adapter 24V2.5A
Compatible	Supported system-XP,Win7,Win8,Win10,ios, Android, Linux, MacOS
Language	
Display language	Support most languages, individual language to be customized
Printing language	Support most languages, individual language to be customized
Packaging/accessories	USB data line - power line adapter - warranty card - Driver CD - Certificate - quick installation guid
Packaging	Color box or kraft Pearl cotton paper tray
Physical	
size	133*135*128mm
color	black
weight	1.288KG
Environment parameters	Storage:-20~70°C∕ working temperature: 0°C - 40°C
	Storage humidity: 5%-95% / working temperature humidity: 20%-85%
Applications:	Restaurant, Department Store, Kitchen, Convenience Store, Specialty Retail, Super mar







Email: marketing@posiflexindia.com | www.posiflexindia.com