



# RP76 V - I

## Barcode Printer

- Fashion appearance
- With high speed, excellent stability and durability
- Paper detection by transmission type, accurately and rapidly
- Imported thermal printer head, printing clearly

### Specification

### RP76 V - I

Print	
Printing Method	Thermal transfer/Direct thermal
Resolution	203dpi
Maximum Print Width	4.09"(104mm)
Maximum Printing Speed	6 ips(152mm/s)
Print Length	0.79"-110"(10-2794mm)
Sensor	Seam mark detection, black mark detection, paper shortage detection, ribbon end detection, cover opening detection, head temperature detection
Type	Coated paper, matt silver paper, wash label, cardboard (hangtag), price tag paper, continuous paper, black label paper, folding paper (rear feed)
Media	
Width (label + backing paper)	0.79"-4.72"(20-120mm)
Length	1200 mm
Thickness (label + backing paper)	0.0023"-0.0098"(0.06mm~0.25mm)
Maximum Paper Roll Diameter	φ5"(φ127mm[MAX])
Reel Inner Diameter	φ1"(φ24mm[MIN])
Carbon Ribbon	
Carbon Ribbon Outer Diameter	φ2.76"(φ70mm[MAX])
Ribbon Length	11.81"(300m)
Ribbon Width	1.57"-4.33"(40-110mm)
Ribbon Core Inner Diameter	φ1"(φ25.4mm[MIN])
Paper Tearing Method	Optional : With cutter (full cut)

Certifications



WPC



V1.0\_13052026

### POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093  
 Tel : +91 80 4078 2700 | Mob : +91 9535432110  
 Email : marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller

Specification	RP76 V - I
Processor	32-bit ARM MCU
RAM	16MB
FLASH	8MB
<b>Function</b>	
Button	Rocker switch, Feed key, Paper bin cover opening key
Indicator Lights	have
Buzzer	Buzzer tone
Display	/
Communication Interface	USB+Ethernet port+Serial port optional: Bluetooth, WIFI
Programming Language	TSPL+ZPL
Built-in Fonts	ASCII Font: 10x12, 14x20, 16x24, 24x32, 36x48, 14x19, 21x27, 14x25, 12x24 GB18030: 24x24
<b>Code Page</b>	
Extended Character Table	CP437,CP850,CP852,CP860,CP863,CP865,CP866, WPC1250, WPC1251, WPC1252, WPC1253, WPC1254
<b>Barcode</b>	
1D	Code 39, 39C, I25, Code 93, ITF25, EAN128, Code 128, Codabar, EAN-8, EAN8+2, EAN8+5, EAN-13, EAN13+2, EAN13+5, UPC-A, UPCA+2, UPCA+5, UPCE, UPCE+2, UPCE+5 MSIC, ITF14, EAN14, CODE11, POST
2D	QRCODE, PDF417, Maxicode, DataMatrix, Aztec, Codablock, Code 49, MicroPDF
<b>Software</b>	
Drive	XP, Win7, Win8, Win10, Win11, Linux, MacOS
SDK	Android, iOS, Windows
Label Design	BarTender barcode label editing software (PC), Bluetooth version: RT ELabel APP (IOS & Android)
<b>Power Adapter</b>	
Input	AC 100-240V, 50/60Hz
Output	DC 24V/2.5A
<b>Environmental Parameters</b>	
Work	Temperature: 32-104°F[0-40°C]; Humidity: 20-90% (non-condensing)
Storage	Temperature: 14-140°F[-10-60°C]; Humidity: 5-95% (non-condensing)
<b>Physical Parameters</b>	
Dimensions	223x168.5x305.1
Weight	2.9Kg
<b>Accessories</b>	
Standard	*Power adapter *Power cord *USB cable *Quick installation guide *Carbon ribbon + paper core
Optional	*Serial port cable *External paper holder A/B *Cutter (full cut)