

RTP-6 V2 & V3

Smart Desktop POS Terminal

- Stable and Durable Touch Performance
- Industrial and Stylish Exterior Design
- Plenty of Peripheral Support and Rich I/O Interface
- Wall Mounted Design that Meets VESA Standards
- Modular Design, Efficient User Service and Extendable 2nd Display



Specification	Variant - 2	Variant - 3
Processor	Intel® core i3	Intel® core i5
Memory	12th Gen, 8G, 256G	12th Gen, 8G, 128G
Display	15.6" PCAP Touch Screen (Bezel Free Display)	
Resolution	Default 1366x768 (HD) / 1920x1080 - FHD (optional)	
OS Support	Win 10 IoT and Win 11 IoT, Linux	
Display Port	VGA x 1 , HDMI X 2 (1 Powered HDMI)	
Serial Port	Dp9X1	
Standard USB Port	USB3.0 X 4 , USB1.0 X 2	
LAN Port	10/1000 Mb x 1	
WiFi / BT	2.4G/5G, latest BT support M.2	
Inbuilt Speaker	2x2W Speaker	
Power Supply	12V,48W adaptor	
Accessoires (option)	10" 2nd display, 1024x600 / MSR	
Dimenstions	380mm x 186mm x 288mm	
Mounting Option	VESA 100x100mm	
Operating Condition	0°C - 40°C, 20%RH - 90%RH	
Storage Condition	-20°C - 60°C, 10%RH - 90%RH	

Main Application Areas:



Certifications	   	V1_10032026
----------------	---	-------------

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093
 Tel : +91 80 4078 2700 | Mob : +91 9535432110
 Email : marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller